, R	EPORT DOC	UMENTATION	N PAGE		OMB No. 0704-0188
Public reporting burden for this maintaining the data needed, a including suggestions for reduc	collection of information is estin nd completing and reviewing thi ing this burden to Department c	nated to average 1 hour per response collection of information. Send f Defense, Washington Headqua	onse, including the time for revie comments regarding this burde rters Services, Directorate for In	nformation Operations as	ching existing data sources, gathering and aspect of this collection of information, and Reports (0704-0188), 1215 Jefferson Davis bject to any penalty for failing to comply with a
collection of information if it doe  1. REPORT DATE (DD)	-MM-YYYY) 2	s should be aware that notwiniste MB control number. PLEASE DO I. REPORT TYPE Technical Papers	O NOT RETURN YOUR FORM		DATES COVERED (From - To)
4. TITLE AND SUBTIT				5a.	CONTRACT NUMBER
				5b.	GRANT NUMBER
	Deas	e se	e . \	5c.	PROGRAM ELEMENT NUMBER
6. AUTHOR(S)	at	Hache	$\mathcal{A}$	/( 5e.	PROJECT NUMBER  OIN  TASK NUMBER
				5f.	WORK UNIT NUMBER
7. PERFORMING ORG	ANIZATION NAME(S)	AND ADDRESS(ES)		8. F	PERFORMING ORGANIZATION PORT
Air Force Research I AFRL/PRS 5 Pollux Drive Edwards AFB CA 9				RE	·
9. SPONSORING / MO	NITORING AGENCY N	AME(S) AND ADDRESS	S(ES)		SPONSOR/MONITOR'S RONYM(S)
Air Force Research	Laboratory (AFMC)			11.	SPONSOR/MONITOR'S NUMBER(S)
5 Pollux Drive Edwards AFB CA 93	3524-7048			P1	easise attached
	VAILABILITY STATEM	IENT		, C	- sesure
	release; distribution				
13. SUPPLEMENTARY	Y NOTES				
14. ABSTRACT					
	·				,
					205 270
		e e		20050	205 278
15. SUBJECT TERMS					
13. SUBJECT TENIVIS					
16. SECURITY CLASS	SIFICATION OF:		17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON Leilani Richardson
a. REPORT	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NUMBER (include area code)
Unclassified	Unclassified	Unclassified	(A)		(661) 275-5015

Form Approved

MEMORANDUM FOR PRS (In-House Publication)

FROM: PROI (STINFO)

19 May 2001

SUBJECT: Authorization for Release of Technical Information, Control Number: AFRL-PR-ED-VG-2001-145
Rusty Blanski, Shawn Phillips, "Status of the Air Force Solid Rocket Motor Insulation Program"

50<sup>th</sup> Annual JANNAF Propulsion Conference (Salt Lake City, UT, 11-13 July 2001) (Deadline: <u>PAST DUE!</u>)

(Statement A)

1. This request has been reviewed by the Foreign Disclosur b.) military/national critical technology, c.) export controls d.) appropriateness for release to a foreign nation, and e.) t Comments:	s or distribution restrictions, echnical sensitivity and/or economic sensitivity.
Signature	Date
2. This request has been reviewed by the Public Affairs Of and/or b) possible higher headquarters review.  Comments:	•
Signature	Date
3. This request has been reviewed by the STINFO for: a.) cb) appropriateness of references, if applicable; and c.) form Comments:	nat and completion of meeting clearance form if required
Signature	
4. This request has been reviewed by PR for: a.) technical a appropriateness of distribution statement, d.) technical sens national critical technology, and f.) data rights and patentab Comments:	accuracy, b.) appropriateness for audience, c.) itivity and economic sensitivity, e.) military/

APPROVED/APPROVED AS AMENDED/DISAPPROVED


Date

PHILIP A. KESSEL
Technical Advisor
Space and Missile Propulsion Division

### Status of the Air Force Solid Rocket Motor Insulation Program

11 July 2001

Dr. Rusty Blanski AFRL/PRSM rusty.blanski@edwards.af.mil








- Introduction
- History of our SRM program: Early Work
- In-House efforts
- **POSS in EPDM Results**
- Future of the Program



### Propulsion (Air Force) Technology is Limited by Material Properties





Toughness, Lightweight & Ease of Processing

·Hybrid plastics can bridge the barrier between ceramics and polymers

#### **POSS**

# Polyhedral OligoMeric Silsesquioxane


interaction at the nano-level (Edwards AFRL/PRSM ---> POSS monomers)₄ The maximization of property enhancements in polymers results from




#### POSS-Polymer Blends Miscibility Demonstrated



50 wt % Phenethyl<sub>8</sub>T<sub>8</sub> in 2 million mol. wt. Polystyrene








- Catalytic hydrogenation of Styryl<sub>8</sub>T<sub>8</sub>
- No POSS crystallites by SEM or X-ray!!



### Versatility of POSS Blends and Lubricants



### **Liquid Rocket Engines**




Polymer Tube/Case Hot Gas Burst Tester

### Plastic Engine Ducting (SSME)

- 80% duct weight decrease
- 15% upper stage thrust-toweight increase
- 3 candidates selected, SBIR, DUS&T

#### Lubricants



## **Lubricants for Turbine Engines**

• Demonstrated to be pour able fractions between – 40 °C and 200 °C


Higher Temperature Studies underway (PRTM)




## **POSS for Ablative Materials**



#### **Traditional Polymer**



#### **POSS Polymer**



increased melt temp





# POSS-Polymer Insulation - Advantages:


- High loadings of POSS can be incorporated without embrittlement
- Si to O ratio is 1:1.5, proven to oxidize up to 1:2 (SiO2)
- Tailorability of POSS monomers improve physical/mechanical properties
- Capabilities for Large and Small scale testing (Hybrid Plastics)



### Solid Propellant Insulation Program Project Goals 6.2 (IHPRPT)



Case Insulation



POSS-Insulation Sample

Goal: 50% Lower Erosion of Insulation (44 % weight reduction, 7.4% booster payload increase) – Phase III IHPRPT Objective: Development of Ceramic Forming Polymer



### Solid Propellant Insulation Program In-House Project History




- 1992: Flame testing performed on POSS-PDMS bead polymers. Potential for SRM insulation recognized
- equipment limitations, a two dimensional test was 1994-1998: 4" Pi-K motor testing begun. Due to designed.
- 1999- present: 3-dimensional cone testing capability acquired. Polymer blending equipment and 24 ton press acquired. Firings begun.



### Solid Propellant Insulation Program In-House Project History 1994-1998





2-D pizza wedges glued into 1/2 cones


- Sample preparation
   was difficult: dissolve
   POSS and polymer in
   solvent, evaporate and
   press into wedge in
   small press
- •Glue sample and standard into test bed (½ cone) and fasten together
- Samples: Pebax, BMI, Parmax, Starfire w/mat



# Solid Propellant Insulation Program



- 3-dimensional testing capability realized
- pressed into Large Pizza was streamlined: POSS with standard industrial is blended into polymer (Brabender Mixer) and Sample preparation wedge (24 ton Press) blending equipment
- standard into cone Glue sample and




Cone, Pizza Wedge and Jig to set wedges in cone






### Present Capabilities:

- Test facilities developed at Edwards AFRL (4" Pi-K Motor)
- Only 100 g of material needed (down from 5 Kg)
- Cost (synthesis, part fabrication, ablation test, analysis) reduced to ~1K‼
- Rapid testing of 5-6 samples per day.







# In-House SRM Insulation Testing



## Interdisciplinary Team Effort

# Many Diverse Skills at AFRL Come Together:

Phenolic cone Fabrication: Machine Shop

Pi-K Motor preparation: Propellants Branch

Pi-K Motor Cutting: Machine Shop

Sample Cone Preparation: Polymer working Group


Sample Firing: Propellants Branch

(measurements) and Motors Branch (mass flux Sample Analysis: Polymer Working Group conversion)

### In-House SRM Insulation Testing Low Cost Screening of New Materials



### CHAR-063 ABLATION






### In-House SRM Insulation Testing Low Cost Screening of New Materials



## CHAR-063 ABLATION

 $(T10 - EPDM/V_8T_8)$ 








### In-House SRM Insulation Testing Ablation Rate Decreased when Using POSS



### CHAR-063 ABLATION RATE


EPDM-Kevlar STANDARD (S10) / EPDM-V<sub>8</sub>T<sub>8</sub> (T10)






### **SRM Insulation Testing Program** Comparisons of POSS in EPDM







# At 50 wt% loadings relative to a proprietary baseline material


	<b>→</b> 20 L 7		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
Hardness:	1%61	no change	17%
Tensile:	<b>2</b> %♦	27%	1%↑
Elongation:	no change	no change	no change
Viscosity:	35%↑	21%	196% ♦
Density:	15%↑	3% ↑	12%↑




# SRM Insulation Testing Program Convergent Cone Testing










- A) Insulation containing POSS monomers
- B) Convergent Cone
- Convergent Cone + Insulation

### **SRM Insulation Testing Program** Convergent Cone SRM Insulation Tests





Negative numbers represent formation of structural char



## SRM Insulation Project What Comes Next?



- More detailed physical testing of insulation
- Multiple sample cone tests
- 50 Firings Planned for FY '02

## SRM Insulation Project Multiple sample/cone



- Presently we are running the tests with two wedges in the cone: a standard and a test sample
- After the test, the cone is cut in half and measurements are taken
- It may be possible to glue in four samples/cone and still get accurate data (3 samples/1 standard)
- Working out the Logistics of multiple samples and Initial Testing is underway
- Payoff- TRIPLING OF SAMPLE OUTPUT

## SRM Insulation Project Future testing



- Thermal Property testing
- density
- specific heat
- thermal conductivity
- SEM analysis before and after
- Char analysis (elemental analysis)

#### Conclusions



- We have all the equipment we need for the rapid testing of Solid Rocket Motor insulation
- Initial Testing in the In-House Pi-K motor tests are promising
- Initial Testing with our Partner on a larger scale also looks promising
- Plans for Future Work (multiple samples, physical testing, sample firings) are underway



### In-House SRM Insulation Testing Acknowledgements



- Mr. Hieu Nguyen (Firing Engineer; Sample Analysis)
- Dr. Tom Hawkins and Greg Warmouth (Motor Firings)
- Mr. Phil Counts (Machine Shop)
- Mr. Pat Ruth (Sample Preparation, measurement)
- Dres Steve Svejda and Shawn Phillips (Moral Support)

Drs